


Cover, Concealed Ceiling Panels

WoodGrain Collection

Concealed acoustic ceiling panels are beautifully simple in design, but the impact is anything but minimal. High-quality woodgrain images are printed on panel covers made of Premier Collection felt, then installed beneath the drop ceiling grid to create a seamless finish. Available in a kaleidoscope of colors and woodgrain prints, Concealed covers are perfect for reducing noise levels in large areas with high footfall as well as smaller spaces where privacy and focus are key.

Specifications

Surface	Ceiling	
Material	FilaSorb™ polyester felt	
Weight	12mm - 2400gsm 24mm - 4800gsm	
Standard Sizes	Width	Length
	600mm W	600mm, 1220mm, 2440mm L
	1220mm W	1220mm, 2440mm L



Cover, Concealed Ceiling Panel in Nordic Plank

Technical

NRC Rating	12mm* 0.45, no air gap 0.85, 200mm air gap 24mm* 0.60, no air gap
Fire Test	Test Results Pending
Water Sorption	ASTM C1104-2019 (A Modified) Water sorbed by weight: 0.20% (based on a 12mm thick panel)
Colorfastness	ISO 105-B02, 6-7

* Test results available upon request.

Details

Lead Time	Refer to Product Lead Time Matrix
Origin	Australia
Warranty	Product: 20 years* Colorfastness: 20 years*

* Conditions apply

Environmental

Recycled Content	Minimum 60%
Energy	Generated using 40% solar energy
Indoor Air Quality	VOC less than/equal to 0.5mg/m3
Recyclable	100%*
Certifications	Declare Certification - LBC Red List Free (third-party verified) SCS Global Indoor Advantage Gold

* PET is recyclable through participating partners.



For questions or additional product information,
visit acoufelt.com.au or call 1800 626 462

Cover, Concealed Ceiling Panels | April 2026

Colorways

WOODGRAIN



Picket Fence
WQ01



Loft
WQ06



White Elm
WQ07



Lyed Larch
WQ30



White Oak
WQ13



Baltic Birch
WQ12




Knotty Spruce
WQ29




French Bobbin
WQ08




Boat Shed
WQ02



Nordic Plank
WQ15




Boardwalk
WQ10




Mocha Legno
WQ25



Mountain Lodge
WQ24




Wine Barrel
WQ03



Log Cabin
WQ04



Natural Oak
WQ16



Woodland Fog
WQ22




Driftwood
WQ21



Weathered Slate
WQ14




Petrified Ash
WQ23




Antique Chest
WQ11



European Larch
WQ17



Fumed Oak
WQ19




Teak
WQ18



Charred Larch
WQ09



Shadow Oak
WQ28



Barn Door
WQ05



Black Walnut
WQ20



Scorched Timber
WQ26



Espresso Oak
WQ27






For questions or additional product information,
visit acoufelt.com.au or call 1800 626 462

Cover, Concealed Ceiling Panels | April 2026

Sizes

Standard Widths 600, 1220mm W

Standard Length 600, 1220, 2440mm L



*Note: For construction adhesive mounting method, panels will have a flush surface.
600mm x 600mm T-grid spacing is required.
T-grid clips are not included; see mounting methods on page 5.*

How to Specify

1. Choose Height

2. Choose Length

3. Choose Colorways

Select height: 600mm or 1220mm H.

1. Choose Height

2. Choose Length

3. Choose Colorways

Concealed panels come in the standard lengths of: 600mm, 1220mm or 2440mm L.

1. Choose Height


2. Choose Length

3. Choose Colorways

See colorway choices on page 3.


Mounting Methods

Direct to 24mm T-grid



**600mm x 600mm T-grid spacing is required.*

Construction adhesive



**For construction adhesive mounting method, panels will have a flush surface.*




For questions or additional product information,
visit acoufelt.com.au or call 1800 626 462

Cover, Concealed Ceiling Panels | April 2026

Acoustic Performance

Test Method	ASTM E795-16
Install Method	A
Rating Method	ISO 11654-1997
Mounting Method	No air gap
Test Results	<p>12mm 0.45, no air gap 0.85, 200mm air gap</p> <p>24mm 0.60, no air gap</p>




	Frequency f (Hz)	125	250	500	1000	2000	4000	NRC
	12mm	0.06	0.02	0.23	0.61	0.89	0.95	0.45
	12mm, 200mm air gap	0.22	0.81	0.90	0.80	0.93	0.99	0.85
	24mm	0.02	0.57	0.41	0.58	0.87	0.85	0.60

What is a Noise Reduction Coefficient (NRC)?

You'll find the NRC rating in the specifications of all of our products. This acronym stands for Noise Reduction Coefficient, and is expressed as a single number, a rating that describes the degree to which acoustic products can absorb sound.

You can use NRC values to understand the overall performance of our acoustic wall and ceiling products. The higher the NRC, the better the product is at soaking up the sound.

Performance Indices: Noise Reduction Coefficient (NRC) results represent the absorption coefficients measured at the one third octave bands at 125, 250, 500, 1000, 2000 and 4000 Hz rounded to the nearest 0.05. Acoustic testing has been performed according to the methods mentioned above. Customization of installation of the product could alter the results. Sound Absorption Average (SAA) indicates the absorption coefficient average for the twelve one-third octave bands ranging between 200 and 2500 Hz.

 For questions or additional product information, visit acoufelt.com.au or call 1800 626 462

Cover, Concealed Ceiling Panels | April 2026