

Flow Ceiling Baffles

Specifications

Application Ceiling

Composition 100% polyester

Material FilaSorb™

Recycled content 60% min. rPET
Thickness 12mm +/- 10%
Weight 2400qsm

Length 2800mm

Custom size available upon request

Height 200 & 400mm

Technical Data

Fire test method EN 13501-1: 2019

Classification B-s1, d0

Water vapour sorption method ASTM C1104-2019 (Procedure A

Modified)

Water sorbed by weight 0.20% (results based on a

12mm thick panel)

Total VOC test method SCS-EC10.3-2014 v4.0 meeting

standard CDPH/EHLB Standard

Method v.1.2-2017

Total VOC result $\leq 0.5 \text{mg/m}^3$

Colourfastness test method ISO 105-B02

Rating 6-7

Sustainability



Made from 60% min. recycled content



Total VOC's less than 0.5 mg/m³ (3rd Party Verified)



Generated using 40% solar energy



Recyclable at end-of-life



Indoor Advantage Gold Certified.









Guarantees

Lead Time 6-8 weeks

Origin United Kingdom
Warranty against defects 20 years*

Colorfastness warranty 20 years*

*conditions apply

Acoustic Performance


Test AS ISO 354-2006: Acoustic - Measurement of **method** sound absorption in a reverberation room

Installation J-600. Sample tested 6 baffles each 2.8m x 0.3m **method** x 12mm, sample hanging 600mm from floor and

152mm apart.

Rating ISO 11654-1997: Acoustic – sound absorbers for **method** use in buildings – rating of sound absorption

Test results NRC 1.30 | aw <1.0 (MH) Class C



Frequency (Hz)	125	250	500	1000	2000	4000	NRC	Class Rating
12mm	0.17	0.44	0.93	1.62	2.20	2.51	1.30	Class C

Performance Indices: **Noise Reduction Coefficient (NRC)** results represent the absorption coefficients measured at the one third octaves bands at 125, 250, 500, 1000, 2000 and 4000 Hz rounded to the nearest 0.05. Acoustic testing has been performed according to the methods mentioned above. Customization of installation of the product could alter the results.



Flow Design

Sizes

Length

2800mm

Custom sizes available

Height 200 & 400mm

Beam Thickness 63.5mm

2800mm

Thickness 12mm

#

Hardware spacing

2800mm

590mm

220mm

Perspective



Ships assembled



FilaSorbTM Colourways



Can't find a colour?

We are constantly updating our palette, which includes adding and discontinuing certain color lines. If you can't find the color you are looking for, please contact us with your color request, as we may still have stock available.



Mounting Methods

Cable Cable to deck Cable to t-grid Cable to Unistrut 2-piece cable coupler with - 15/16" flat T-grid (by others) P1000 series Unistrut (by others) 1/4"-20 female thread Aircraft cable Aircraft cable & spring channel nut assembly Twist lock Aircraft cable Cable gripper Aircraft cable Cable gripper assembly assembly Cable gripper – Baffle Baffle Cable gripper assembly Baffle – Baffle

