

Framework, Open

Ceiling Grids

WoodGrain Collection

The Framework design provides a cushion of quiet while keeping the aesthetic of an open ceiling within any environment. Offering flexibility for different size spaces, Framework is available in three cell size options: 610mm x 610mm, 914mm x 914mm, and 1219mm x 1219mm. Additionally, Framework works seamlessly around other ceiling components such as sprinklers, speakers, and lighting.

Specifications

Surface	Ceiling		
Material	FilaSorb™ polyester felt		
Weight	2400 gsm		
Standard Sizes	**Cell**	**Height**	**Thickness**
	600 x 600mm 900 x 900mm 1200 x 1200mm *Custom sizes available*	150, 200, 255mm H	50, 75, or 100mmT



Framework, Open Ceiling Grids in Charred Larch

Technical

NRC Rating	1.65*
Fire Test	AS ISO 9705:2003 according to AS 5637.1:2015 requirements Group 1 0.93
Water Sorption	ASTM C1104-2019 (A Modified) Water sorbed by weight: 0.20% (based on a 12mm thick panel)
Colorfastness	ISO 105-B02, 6-7

** Test results available upon request*

Details

Lead Time	Refer to Product Lead Time Matrix
Origin	Australia
Warranty	Product: 20 years* Colorfastness: 20 years*

** Conditions apply*

Environmental

Recycled Content	Minimum 60%
Energy	Generated using 40% solar energy
Indoor Air Quality	VOC less than/equal to 0.5mg/m3
Recyclable	100%*
Certifications	Declare Certification - LBC Red List Free (third-party verified) SCS Global Indoor Advantage Gold

** PET is recyclable through participating partners*

© 2026 Acoufelt. All rights reserved.

Colorways

WOODGRAIN



Picket Fence
WQ01



Loft
WQ06



White Elm
WQ07



Lyed Larch
WQ30



White Oak
WQ13



Baltic Birch
WQ12




Knotty Spruce
WQ29



French Bobbin
WQ08



Boat Shed
WQ02



Nordic Plank
WQ15




Boardwalk
WQ10



Mocha Legno
WQ25



Mountain Lodge
WQ24



Wine Barrel
WQ03



Log Cabin
WQ04



Natural Oak
WQ16



Woodland Fog
WQ22




Driftwood
WQ21



Weathered Slate
WQ14




Petrified Ash
WQ23




Antique Chest
WQ11



European Larch
WQ17



Fumed Oak
WQ19



Teak
WQ18



Charred Larch
WQ09



Shadow Oak
WQ28



Barn Door
WQ05



Black Walnut
WQ20



Scorched Timber
WQ26




Espresso Oak
WQ27


© 2026 Acoufelt. All rights reserved.


Sizes

Standard Sizes	Cell	Height	Thickness
	600mm x 600mm 900mm x 900mm 1200mm x 1200mm *Custom sizes available*	150, 200, 255mm H	50, 75, 100mmT


Plans










Elevations







Perspectives








© 2026 Acoufelt. All rights reserved.

How to Specify


1. Choose Grid Size | **2. Choose Slat Sizes** | **3. Choose Colorways**

Grids are available in three size: 600mm x 600mm, 900mm x 900mm, and 1200mm x 1200mm.


600mm x 600mm



900mm x 900mm



1200mm x 1200mm



---

1. Choose Cell Size | **2. Choose Slat Sizes** | **3. Choose Colorways**


Slats are available in 2 size options.

A: Consistent Sizes



Slat Size
50mm T x 150mm H
50mm T x 200mm H
50mm T x 275mm H
75mm T x 150mm H
75mm T x 200mm H
75mm T x 275mm H
100mm T x 150mm H
100mm T x 200mm H
100mm T x 275mm H

B: Varied Sizes



Height ratio from Slat 1 to Slat 2 is 2:1

Slat 1 Size	Slat 2 Size
50mmT x 75mmH	50mmT x 150mmH
50mmT x 100mmH	50mmT x 200mmH
50mmT x 125mmH	50mmT x 255mmH
75mmT x 75mmH	75mmT x 150mmH
75mmT x 100mmH	75mmT x 200mmH
75mmT x 125mmH	75mmT x 255mmH
100mmT x 75mmH	100mmT x 150mmH
100mmT x 100mmH	100mmT x 200mmH
100mmT x 125mmH	100mmT x 255mmH
50mmT x 75mmH	100mmT x 150mmH
50mmT x 100mmH	100mmT x 200mmH
50mmT x 125mmH	100mmT x 255mmH
100mmT x 75mmH	50mmT x 150mmH
100mmT x 100mmH	50mmT x 200mmH
100mmT x 125mmH	50mmT x 255mmH

---


1. Choose Slat Size | **2. Choose Backer Panel Size** | **3. Choose Colorways**

See colorway choices on the page 3.


© 2026 Acoufelt. All rights reserved.

Mounting Methods


Cable




Cable to deck




Swivel cable to deck




Cable to T-grid



Threaded Rod




Magnet to T-grid



© 2026 Acoufelt. All rights reserved.


Twist lock to T-grid



© 2026 Acoufelt. All rights reserved.

Acoustic Performance

Test Method	ASTM E795-16
Install Method	J-600
Rating Method	ASTM C423-17
Mounting Method	Sample tested 6 baffles 2794mmL x 305mm D x 75mm thickness, hanging 600mm from floor and152mm from each other
Test Results	NRC 1.65 SAA 1.68



Frequency f (Hz)	125	250	500	1000	2000	4000	NRC
76mm Truss Baffle	0.26	0.86	1.25	2.02	2.49	2.49	1.65

What is a Noise Reduction Coefficient (NRC)?

You'll find the NRC rating in the specifications of all of our products. This acronym stands for Noise Reduction Coefficient, and is expressed as a single number, a rating that describes the degree to which acoustic products can absorb sound.

You can use NRC values to understand the overall performance of our acoustic wall and ceiling products. The higher the NRC, the better the product is at soaking up the sound.

Performance Indices: Noise Reduction Coefficient (NRC) results represent the absorption coefficients measured at the one third octave bands at 125, 250, 500, 1000, 2000 and 4000 Hz rounded to the nearest 0.05. Acoustic testing has been performed according to the methods mentioned above. Customization of installation of the product could alter the results. Sound Absorption Average (SAA) indicates the absorption coefficient average for the twelve one-third octave bands ranging between 200 and 2500 Hz.

© 2026 Acoufelt. All rights reserved.