





Pendant, Diamond Ceiling Clouds

Premier Collection

Transform sound absorption into grand-scale art. Blend and suspend Pendant, Diamond Ceiling Clouds in varying colors and sizes to create a distinct, beautifully performing sculptural installation. Precision fabrication, combined with an invisible structure and lightweight design, is ideal in high-volume, high-profile spaces.

Specifications

Surface	Ceiling
Material	FilaSorb™ polyester felt
Weight	2400gsm
Standard Sizes	Width: 241mm, 343mm, and 445mm W Length: 394mm, 572mm, and 749mm L Heights: Range from 610mm up to 2743mm H



Pendant, Diamond Ceiling Cloud in Celery, Sencha and Kale

Technical

NRC Rating	0.45*
Fire Test	Test Results Pending
Water Sorption	ASTM C1104-2019 (A Modified) Water sorbed by weight: 0.20% (based on a 12mm thick panel)
Colorfastness	ISO 105-B02, 6-7

* Test results available upon request

Details

Lead Time	Refer to Product Lead Time Matrix
Origin	Australia
Warranty	Product: 20 years* Colorfastness: 20 years*

* Conditions apply

Environmental


































Recycled Content	Minimum 60%
Energy	Generated using 40% solar energy
Indoor Air Quality	VOC less than/equal to 0.5mg/m3
Recyclable	100%*
Certifications	Declare Certification - LBC Red List Free (third-party verified) SCS Global Indoor Advantage Gold

* PET is recyclable through participating partners



For questions or additional product information,
visit acoufelt.com.au or call 1800 626 462

Pendant, Diamond Ceiling Clouds | May 2026

							
White WH12	Milkyway MI74	Ivory IV11	Pearl PE21	Valentine VA70	Quartz QU67	Stonewash ST72	Sea Salt SE57
							
Platinum PL04	Almond AL55	Pistachio PI25	Turmeric TU60	Flamingo FL61	Amethyst AM69	Periwinkle PE23	Peacock PE20
							
Metal ME03	Mushroom MU75	Celery CE65	Wheat WH68	Peach PE19	Lilac LI13	Marine MA15	Senna SE58
							
Grey GR02	Umber UM54	Wasabi WA29	Popcorn PO26	Currant CU59	Berry BE06	Azure AZ05	Oregano OR18
							
Charcoal CH01	Walnut WA56	Eucalyptus EU71	Carrot CA08	Loganberry LO77	Granite GR62	Denim DE09	Kale KA12
							
Piano Black PI24	Slate SL27	Nori NO76	Peppercorn PE22	Shiraz SH63	Flint FL64	Midnight MI16	




For questions or additional product information,
visit acoufelt.com.au or call 1800 626 462

Pendant, Diamond Ceiling Clouds | May 2026


Sizes

Standard Sizes Width: 241mm, 343mm, and 445mm W
Length: 394mm, 572mm, and 749mm L
Heights: Range from 610mm up to 2743mm H


Plan



Perspective






Elevations



Hardware Spacing


241mm W	51mm on center spacing,
343mm W	102mm on center spacing
445mm W	127mm on center spacing

394mm L	88mm on center spacing,
572mm L	176mm on center spacing
749mm L	220mm on center spacing



Recommended Layouts


Layout 1



Layout 2



Layout 3



How to Specify

1. Choose Width

2. Choose Height

3. Choose Layout

4. Choose Colorways

Pendant, Diamond comes in 3 widths that can mix and match to meet your desired design: 241mm, 343mm, or 445mm W.

1. Choose Width

2. Choose Height

3. Choose Layout

4. Choose Colorways

Choose heights from 610mm up to 2743mm H. Sizes can be mixed to achieved desired design.

1. Choose Width

2. Choose Height

3. Choose Layout

4. Choose Colorways

See page 5 for recommended layouts.

1. Choose Width

2. Choose Height

3. Choose Layout

4. Choose Colorways

See colorway choices on page 3.




For questions or additional product information,
visit [acoufelt.com.au](https://www.acoufelt.com.au) or call 1800 626 462


Pendant, Diamond Ceiling Clouds | May 2026

Mounting Methods


Cable



Cable to deck



Threaded rod




For questions or additional product information,
visit acoufelt.com.au or call 1800 626 462

Pendant, Diamond Ceiling Clouds | May 2026

Acoustic Performance

Test Method	ASTM C423-17
Install Method	Type A
Rating Method	ISO 11654-2007
Test Results	NRC 0.45, no air gap SAA 0.43



Frequency f (Hz)	125	250	500	1000	2000	4000	NRC
12mm	0.06	0.02	0.23	0.61	0.89	0.95	0.45

What is a Noise Reduction Coefficient (NRC)?

You'll find the NRC rating in the specifications of all of our products. This acronym stands for Noise Reduction Coefficient, and is expressed as a single number, a rating that describes the degree to which acoustic products can absorb sound.

You can use NRC values to understand the overall performance of our acoustic wall and ceiling products. The higher the NRC, the better the product is at soaking up the sound.

Performance Indices: Noise Reduction Coefficient (NRC) results represent the absorption coefficients measured at the one third octave bands at 125, 250, 500, 1000, 2000 and 4000 Hz rounded to the nearest 0.05. Acoustic testing has been performed according to the methods mentioned above. Customization of installation of the product could alter the results. Sound Absorption Average (SAA) indicates the absorption coefficient average for the twelve one-third octave bands ranging between 200 and 2500 Hz.



For questions or additional product information, visit acoufelt.com.au or call 1800 626 462

Pendant, Diamond Ceiling Clouds | May 2026