acoufelt



Pixel


Ceiling Panels

Premier Collection


Pixel is a double-layer acoustic panel that pairs minimalist design with maximum impact. Precision-cut patterns in the face of the outer felt layer reveal a contrasting second layer beneath to create depth, texture, and visual interest. Classic shapes add color and dimension while delivering premium sound absorption. Choose any two colors from the Premier palette to customize your Pixel pattern.

Specifications

Surface	Ceiling
Material	FilaSorb™ polyester felt
Weight	14mm, 2400gsm 24mm, 4800gsm
Standard Sizes	Width: 610mm, 1220mm W Length: 610mm, 1220mm and 2440mm L



Pixel Ceiling Panel with Rectangle Pattern in Flint and Almond



Pixel Ceiling Panel with Circle Pattern in Midnight, Periwinke and Wheat

Technical

NRC Rating	**14mm*** 0.55, no air gap 0.70, 20mm air gap 0.75, 50mm air gap **24 mm*** 0.60, no air gap
Fire Test	Test Results Pending
Water Sorption	ASTM C1104-2019 (A Modified) Water sorbed by weight: 0.20% based on a 12mm thick panel)
Colorfastness	ISO 105-B02, 6-7

** Test results available upon request*

Details

Lead Time	Refer to Product Lead Time Matrix
Origin	Australia
Warranty	Product: 20 years* Colorfastness: 20 years*

** Conditions apply*

Environmental

Recycled Content	Minimum 60%
Energy	Generated using 40% solar energy
Indoor Air Quality	VOC less than/equal to 0.5mg/m3
Recyclable	100%*
Certifications	Declare Certification - LBC Red List Free (third-party verified) SCS Global Indoor Advantage Gold

** PET is recyclable through participating partners*

© 2026 Acoufelt. All rights reserved.

Colorways

White
WH12


Milkyway
MI74


Ivory
IV11

Pearl
PE21


Valentine
VA70


Quartz
QU67


Stonewash
ST72


Sea Salt
SE57


Platinum
PL04


Almond
AL55


Pistachio
PI25


Turmeric
TU60


Flamingo
FL61


Amethyst
AM69


Periwinkle
PE23


Peacock
PE20


Metal
ME03


Mushroom
MU75


Celery
CE65


Wheat
WH68


Peach
PE19


Lilac
LI13


Marine
MA15


Sencha
SE58


Grey
GR02


Umber
UM54


Wasabi
WA29


Popcorn
PO26


Currant
CU59


Berry
BE06


Azure
AZ05


Oregano
OR18


Charcoal
CH01


Walnut
WA56


Eucalyptus
EU71


Carrot
CA08


Loganberry
LO77


Granite
GR62


Denim
DE09


Kale
KA12

Piano Black
PI24

Slate
SL27

Nori
NO76

Peppercorn
PE22

Shiraz
SH63

Flint
FL64


Midnight
MI16

© 2026 Acoufelt. All rights reserved.


Sizes


Standard Sizes Width: 610mm, 1220mm W
Length: 610mm, 1220mm and 2440mm L

Plan



Perspective






© 2026 Acoufelt. All rights reserved.


How to Specify

1. Choose Panel Design | **2. Choose Sizes** | **3. Choose Colorways**


Select desired panel design.




CIRCLE




SQUARE



TRIANGLE



RECTANGLE




RIGHT TRIANGLE

1. Choose Panel Design | **2. Choose Sizes** | **3. Choose Colorways**

Select desired height and width.

1. Choose Panel Design | **2. Choose Sizes** | **2. Choose Colorways**

Select two colors: one for the face panel and one for the back panel to create a Pixel that is uniquely yours. See colorways on page 3.




Square in Marine and Sea Salt

© 2026 Acoufelt. All rights reserved.

Mounting Methods


Direct to 24mm T-grid



© 2026 Acoufelt. All rights reserved.

Acoustic Performance

Test Method	ISO 354-2006
Install Method	A
Rating Method	ISO 11654-2002
Test Results	**14mm** NRC 0.55, no air gap NRC 0.70, 20mm air gap NRC 0.75, 50mm air gap SAA 0.56, no air gap SAA 0.70, 20mm air gap SAA 0.76 50mm air gap **24mm** NRC 0.60, no air gap



	Frequency f (Hz)	125	250	500	1000	2000	4000	NRC
	14mm	0.01	0.11	0.37	0.78	1.00	0.98	0.55
	14mm, 20mm air gap	0.03	0.22	0.61	0.93	1.03	0.94	0.70
	14mm, 50mm air gap	0.06	0.44	0.78	0.92	0.92	0.93	0.75
	24mm	0.02	0.57	0.41	0.58	0.87	0.85	0.60

What is a Noise Reduction Coefficient (NRC)?

You'll find the NRC rating in the specifications of all of our products. This acronym stands for Noise Reduction Coefficient, and is expressed as a single number, a rating that describes the degree to which acoustic products can absorb sound.

You can use NRC values to understand the overall performance of our acoustic wall and ceiling products. The higher the NRC, the better the product is at soaking up the sound.

Performance Indices: Noise Reduction Coefficient (NRC) results represent the absorption coefficients measured at the one third octave bands at 125, 250, 500, 1000, 2000 and 4000 Hz rounded to the nearest 0.05. Acoustic testing has been performed according to the methods mentioned above. Customization of installation of the product could alter the results. Sound Absorption Average (SAA) indicates the absorption coefficient average for the twelve one-third octave bands ranging between 200 and 2500 Hz.

© 2026 Acoufelt. All rights reserved.