

Pixel Wall Panels

Product Detail

Technical Data

Guarantees

Warranty against defects

Colourfastness warranty

Lead time

Origin

Application Wall Composition 100% polyester Material FilaSorb™ Recycled content 60% min Weight 2800 & 4800gsm Thickness 14mm +/- 10% (2mm backer panel + 12mm finish panel) 24mm +/- 10% (12mm backer panel + 12mm finish panel) 1200 x 2780mm Dimensions Custom size available upon request

14mm & 24mm	
Fire test	Pending
14mm & 24mm	
Total VOC test method	SCS-EC10.3-2014 v4.0 meeting standard CDPH/EHLB Standard Method v.1.2-2017
Total VOC result	≤ 0.5mg/m ³
Colourfastness test method	ISO 105-B02
Rating	6-7
Water vapour sorption meth	od ASTM C1104-2019 (Procedure A Modified)
Water sorbed by weight	0.20% (results based on a 12mm thick panel)

4-6 weeks

20 years*

20 years*

*conditions apply

United Kingdom

Acoustic Performance

Test method

14mm AS ISO 354-2006: Acoustic - Measurement of sound absorption in a reverberation room

Method

Installation metho

Mounting method A

Rating method and sytems

Test results 14mm

24mm



Frequency (Hz)	125	250	500	1000	2000	4000	NRC
14mm - a _s no air gap	0.00	0.10	0.40	0.80	1.00	1.00	0.55
14mm - a _s 20mm air gap	0.05	0.25	0.60	0.95	1.00	0.95	0.70
14mm - α _s 50mm air gap	0.10	0.45	0.75	0.90	0.90	0.90	0.75
24mm	0.02	0.57	0.41	0.58	0.87	0.85	0.60

Performance Indices: Noise Reduction Coefficient (NRC) results represent the absorption coefficients measured at the one third octaves bands at 125, 250, 500, 1000, 2000 and 4000 Hz rounded to the nearest 0.05. Acoustic testing has been performed according to the methods mentioned above. Customisation of installation of the product could alter the results.

Sustainability



Made from 60% min. recycled content



Total VOC's less than 0.5 mg/m³







Recyclable at end of lifespan



24mm ASTM C423-17: Standard Test Method for Sound Absorption and Sound Absorption Coefficients by the Reverberation Room

		i	
Q		1	
١			
	۰.		

AS ISO 11654 -2002: Acoustics - rating of sound absorption - material

no air gap - 0.55 NRC | 0.40 (M/H) aw, Class D 20mm air gap - 0.70 NRC | 0.55 (MH) aw, Class D 50mm air gap - 0.75 NRC | 0.75 (MH) aw, Class C

0.60 NRC no air gap | 0.50 (LH) aw, Class D



Designs

	0	0	0	0	0	0	0	0] [Δ	Δ	Δ	Δ	Δ	Δ	Δ	Δ					⊿	⊿	Δ	⊿	Δ	Δ	⊿	⊿				
	0	0	0	0	0	0	0	0			Δ	Δ	Δ	Δ	Δ	Δ						⊿	⊿	⊿	⊿	⊿	⊿	⊿	⊿				
	0	0	0	0	0	0	0	0			Δ	Δ	Δ	Δ	Δ	Δ						⊿	⊿	⊿	⊿	Δ	⊿	⊿	⊿				
	0	0	0	0	0	0	0	0			Δ	Δ	Δ	Δ	Δ	Δ						⊿	⊿	⊿	⊿	⊿	⊿	⊿	⊿				
	0	0	0	0	0	0	0	0			Δ	Δ	Δ	Δ	Δ	Δ						⊿	⊿	⊿	⊿	⊿	⊿	⊿	⊿				
	0	0	0	0	0	0	0	0			Δ	Δ	Δ	Δ	Δ	Δ						⊿	⊿	⊿	⊿	⊿	⊿	⊿	⊿				
	0	0	0	0	0	0	0	0			Δ	Δ	Δ	Δ	Δ	Δ						⊿	⊿	⊿	⊿	⊿	⊿	⊿	⊿				
	0	0	0	0	0	0	0	0			Δ	Δ	Δ	Δ	Δ	Δ						⊿	⊿	⊿	⊿	⊿	⊿	Δ	⊿				
	0	0	0	0	0	0	0	0			Δ	Δ	Δ	Δ	Δ	Δ						⊿	⊿	⊿	⊿	⊿	⊿	Δ	⊿				
	0	0	0	0	0	0	0	0			Δ	Δ	Δ	Δ	Δ	Δ						⊿	⊿	⊿	⊿	Δ	⊿	⊿	⊿				
	0	0	0	0	0	0	0	0			Δ	Δ	Δ	Δ	Δ	Δ						⊿	⊿	⊿	⊿	Δ	⊿	⊿	⊿				
	0	0	0	0	0	0	0	0			Δ	Δ	Δ	Δ	Δ	Δ						⊿	⊿	⊿	Δ	Δ	⊿	⊿	⊿				
	0	0	0	0	0	0	0	0			Δ	Δ	Δ	Δ	Δ	Δ						⊿	⊿	⊿	⊿	Δ	⊿	⊿	⊿				
	0	0	0	0	0	0	0	0			Δ	Δ	Δ	Δ	Δ	Δ						⊿	⊿	⊿	Δ	⊿	⊿	⊿	⊿				
	0	0	0	0	0	0	0	0			Δ	Δ	Δ	Δ	Δ	Δ						⊿	Δ	⊿	⊿	⊿	⊿	⊿	⊿				
	0	0	0	0	0	0	0	0			Δ	Δ	Δ	Δ	Δ	Δ						⊿	⊿	⊿	⊿	⊿	⊿	⊿	⊿				
	0	0	0	0	0	0	0	0			Δ	Δ	Δ	Δ	Δ	Δ						⊿	⊿	⊿	⊿	⊿	⊿	⊿	⊿				
	0	0	0	0	0	0	0	0			Δ	Δ	Δ	Δ	Δ	Δ						⊿	⊿	⊿	⊿	⊿	⊿	⊿	⊿				
_																																	

Circle

Triangle

Square

Right Triangle

Rectangle



14mm Design Profile





24mm Design Profile





FilaSorbTM Colourways



Can't find a colour?

We are constantly updating our palette, which includes adding and discontinuing certain colour lines. If you can't find the colour you are looking for, please contact us with your colour request, as we may still have stock available.





Oregano OR18



Sencha SE58





Azur AZ05



Platinum PL04



Marine MA15



Milkyway MI74



Colour Scheme Examples



Pistachio (Finish Panel) + Walnut (Backer Panel)

Marine (Finish Panel) + Sea Salt (Backer Panel) Valentine (Finish Panel) + Almond (Backer Panel) Eucalyptus (Finish Panel) + Celery (Backer Panel)



Walnut (Finish Panel) + Piano Black (Backer Panel)

