

Printed Ceiling Panel

acoutelt making quiet

QuietPrint™

Product Detail

Application Ceiling

Composition100% polyesterMaterialFilaSorb™

Recycled content 60% min

Dimensions 1220 x 2800mm

Custom sizes available upon request

Thickness 12mm +/- 10%

Guarantees

Warranty against defects 20 years* Light fastness warranty 20 years*

*conditions apply

QuickShip

QuickShip Custom



Custom products have an approx. **6–8 week** lead time from payment and order confirmation.

Technical Data

Fire rating AS/ISO 9705.1, Group 1

ASTM E84-17a, Class A

EN 13501-1: 2019, B-s1, d0

Indoor air quality SCS-EC10.3-2014 v4.0 meeting

standard CDPH/EHLB Standard Method

 $v.1.2-2017, \le 0.5 \text{mg/m}^3$

Light fastness ISO 105-B02, 6-7

Sustainability



Made from 60% min. recycled content



Red List Free Declare Label



Generated using 40% solar energy



Recyclable at end-of-life



Total VOC's less than 0.5 mg/m³ (3rd Party Verified)



Phenol & formaldehyde free








Acoustic Performance

Test method ISO 354-2006

Results NRC 0.45 (no air gap)


NRC 0.54 (12mm air gap) NRC 0.64 (20mm air gap) NRC 0.85 (200mm air gap)



	Frequency (Hz)	125	250	500	1000	2000	4000	NRC
	as no air gap	0.06	0.02	0.23	0.61	0.89	0.95	0.45
	as 12mm air gap	0.03	0.14	0.33	0.74	1.00	1.00	0.54
	as 20mm air gap	0.05	0.16	0.48	0.85	1.00	1.00	0.64
	as 200mm air gap	0.40	0.75	0.90	0.85	0.95	1.00	0.85



Colorways



Mounting Methods

Adhesive Me thod Panel installation area Construction adhesive Panel installation area Spray adhesive

