



QuietBack™ Carpet Tile Acoufelt

Final Assembly: Muang, Chonburi Thailand

Life Expectancy: 20 Year(s)

Embodied Carbon: 1.44 kg CO2 eq

Declared Unit: 1 sqm

End of Life Options: Salvageable/Reusable in its Entirety

Ingredients:

Coating: Aluminum hydroxide; 1-Propene, polymer with ethene; Calcium Carbonate; Petroleum resins; Styrene-butadiene copolymers; Water; Amorphous silica; C.I. Pigment Black 6; **Felt Backing:** Polyethylene Terephthalate; **Pile Face:** Nylon 6; **Primary Backing Non-Woven:** Polyethylene Terephthalate; Nylon 6; **Surface Treatment:** 2-Propenoic acid, 2-methyl-, polymer with ethyl 2-propenoate and methyl 2-methyl-2-propenoate; Cutting Oils

Living Building Challenge Criteria: Compliant

I-13 Red List:

- | | |
|---|-----------------------------|
| <input checked="" type="checkbox"/> LBC Red List Free | % Disclosed: 100% at 100ppm |
| <input type="checkbox"/> LBC Red List Approved | VOC Content: Not Applicable |
| <input type="checkbox"/> Declared | |

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

ACF-0001

EXP. 01 JUN 2025

Original Issue Date: 2019

MANUFACTURER RESPONSIBLE FOR LABEL ACCURACY

INTERNATIONAL LIVING FUTURE INSTITUTE™ living-future.org/declare