

Swing Clouds



Specifications

Technical Data

Acoustic Performance

Application	Ceiling
Material	FilaSorb™ polyester felt
Recycled content	60% min. rPET
Thickness	12mm +/- 10%
Weight	2400gsm
Dimensions	102 x 610 x 305mm (T x W x H) 102 x 915 x 457mm (T x W x H) 102 x 1220 x 610mm (T x W x H) Lengths – 610 or 1220mm

Fire test method Group number SMOGRARC (in m2/s2 x 1000)	AS ISO 9705:2033 (according to AS 5637.7:2015 requirements) Group 1 0.93	Test method Installation method
Total VOC test method Total VOC result	SCS-EC10.3-2014 v4.0 meeting standard CDPH/EHLB Standard Method v.1.2-2017 ≤ 0.5mg/m ³	Rating method Test results
Colorfastness test method Rating	ISO 105-B02 6-7	
Water vapour sorption method	ASTM C1104-2019 (Procedure A Modified)	
Water sorbed by weight	0.20% (results based on a 12mm thick panel)	

Sustainability



Made from 60% min. recycled content



Material 'Take Back' program allows our product to be recycled

Lead time	3-6 weeks
Origin	Australia
Warranty against defects	20 years*
Colorfastness warranty	20 years*
	*conditions apply

Details



Acoustic Felt material is made with 30-40% solar energy* "made in Thailand





- Pending product testing
- Pending product testing
- Pending product testing
- esults Pending product testing



Design

Sizes

Width x Heigh	t 1220 W x 610mm H 915 W x 475mm H 610 W x 305mm H
Length	610 & 1220mm
Thickness	102mm

Front Elevation







Hardware Spacing

610mm – 305mm on centre spacing

915mm – 457mm on centre spacing

1220mm – 610mm on centre spacing



















FilaSorb[™] Colorways



Can't find a color?

We are constantly updating our palette, which includes adding and discontinuing certain color lines. If you can't find the color you are looking for, please contact us with your color request, as we may still have stock available.





Oregano OR18





Azur AZ05





Platinum PL04



Sencha SE58



Marine MA15



Walnut WA56



WoodBeQuiet[™] Prints







Charred Larch WQ09



Fumed Oak WQ19



Knotty Spruce WQ29



Boardwalk WQ10



Black Walnut WQ20



Lyed Larch WQ30



Mounting Methods

Cable



Cable to deck

Swivel cable to deck



Cable to t-grid



	- P1000 series Unistrut (by others) - Aircraft cable & spring channel nut assembly
	Washer
	2-piece cable coupler with 1/4"-20 female thread
	Cable gripper assembly
	Nut plate
	- Baffle

Cable to Unistrut

